



Meets MIL-STD-348A, MIL-C-39012, CECC 22110 and IEC60169-15.

**TECHNICAL CHARACTERISTICS**

Impedance	50Ω	Frequency Range	DC-27GHz
Working Voltage	335V r.m.s	Withstanding Voltage	1000V r.m.s
Center Contact Resistance	≤3mΩ	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.25
Durability	≥500 cycles	Temperature Range	-55°C to 155°C
Weight	4.16g Ref.		

3	Contact	1	Beryllium	Gold
2	Insulator	1	PEI	
1	Body	1	Stainless Steel	Passivated
No.	Description	QTY	Material	Finish

**RoHS  
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES			
SCALE	1:1	UNIT	MM

APPROVED <b>JOHN</b>
CHECKED <b>TERRY</b>
DRAWN <b>TINA</b>
DRAWN DATE 15 Mar. 2013

<b>KM</b> KeMy Electronic Technology Inc.	
TITLE <b>SMA (F) Jack to SMA (M) Plug Adapter</b>	
DRAWING NO. <b>KM-030115-SS</b>	REV 0