



Meets MIL-STD-348A, MIL-C-39012, CECC 22110 and IEC60169-15.

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC-26.5GHz
Working Voltage	335V r.m.s	Withstanding Voltage	1000V r.m.s
Center Contact Resistance	≤3mΩ	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.20 @ 18GHz
Durability	≥500 cycles	Temperature Range	-55°C to 155°C
Weight	4.40g Ref.		

3	Contact	1	Beryllium	Gold
2	Insulator	1	PTFE	
1	Body	1	Stainless Steel	Passivated
No.	Description	QTY	Material	Finish
8				

**RoHS
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES	APPROVED JOHN
	CHECKED TERRY
	DRAWN TINA
SCALE 1:1 UNIT MM	DRAWN DATE 15 Mar. 2013

KEM KeMy Electronic Technology Inc.

TITLE
**SMA (M) Plug to SMA (M)
Plug Adapter**

DRAWING NO. **KM-030116-SS**

REV
0