



Meets MIL-C-39012, IEC60169-16, IEC60169-12, CECC 22210, GB/T 15888.  
Precision Machined and High Quality Material.

**TECHNICAL CHARACTERISTICS**

Impedance	50Ω	Frequency Range	DC ~ 300MHz
Working Voltage	750V r.m.s	Withstanding Voltage	2000V r.m.s
Center Contact Resistance	≤5mΩ	Outer Contact Resistance	≤5mΩ
Insulation Resistance	≥5000MΩ	Durability	≥500 cycles
Temperature Range	-55°C to 155°C	Weight	31.17g Ref.

3	Contact	1	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish
8				
7				
6				
5				
4				
3				

**RoHS Compliant**

THIRD ANGLE PROJECTION

\* MAJOR DIMENSION  
UNLESS OTHERWISE NOTED TOLERANCES

SCALE 1:1 UNIT MM

APPROVED JOHN  
CHECKED TERRY  
DRAWN HENRY  
DRAWN DATE 06 Mar. 2011

**KM** KeMy Electronic Technology Inc.  
TITLE N (M) Plug to UHF (F) Jack SO-239 Adapter  
DRAWING NO. KM-030138-G  
REV 0