



RECOMMENDED
PANEL CUTOUT

Meets MIL-C-39012, CECC 22200, CECC 22220, IEC60169-17, IEC60169-36
Precision Machining and High Quality Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC ~ 3GHz
Working Voltage	250V r.m.s	Withstanding Voltage	<750V r.m.s
Center Contact Resistance	≤5mΩ	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥1000MΩ	Durability	≥500 cycles
Temperature Range	-55°C to 155°C		

6	Nut	1	Brass	Nickel
5	Washer	1	SUS304	Passivation
4	Gasket	1	Silicone	
3	Contact	1	Be. Bronze	Gold
2	Insulator	2	PTFE	
1	Body	1	Brass	Nickel

**RoHS
Compliant**

© THIRD ANGLE PROJECTION

* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES	APPROVED JOHN
	CHECKED TERRY
	DRAWN KEVIN
SCALE 1:1 UNIT MM	DRAWN DATE 13 Sep. 2005

KEM KeMy Electronic Technology Inc.

TITLE
**TNC (F) Jack to MCX (F) Adapter,
Bulkhead, Waterproof**

DRAWING NO. **KM-030172-2**

REV
0