



RECOMMENDED MOUNTING HOLE

Meets MIL-C-39012, CECC 22210, CECC 22220, IEC60169-16, IEC60169-36.
Precision Machining and High Quality Grade Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC-6GHz
Working Voltage	<250V r.m.s	Withstanding Voltage	750V r.m.s
Center Contact Resistance	≤5Ω	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥1000MΩ	VSWR	≤1.25
Durability	≥500 cycles	Temperature Range	-55°C to 155°C

4	Gasket	1	Silicone	
3	Contact	1	Phos. Bronze	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish

**RoHS
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION
UNLESS OTHERWISE
NOTED TOLERANCES

SCALE 1:1 UNIT MM

APPROVED
JOHN

CHECKED
TERRY

DRAWN
KEVIN

DRAWN DATE
28 Apr. 2015

KM KeMy Electronic Technology Inc.

TITLE
N (F) Jack to MCX (F) Jack Adapter,
4-hole Flange Mount, Waterproof

DRAWING NO. **KM-030173**

REV
0