



Meets MIL-C-39012, CECC 22110, CECC 22220, IEC60169-15, IEC60169-36
Precision Machining and High Quality Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC ~ 6GHz
Working Voltage	250V r.m.s	Withstanding Voltage	<750V r.m.s
Center Contact Resistance	≤5mΩ	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥1000MΩ	Durability	≥500 cycles
Temperature Range	-55°C to 155°C		

6	Nut	1	Brass	Gold
5	Washer	1	Brass	Gold
4	Gasket	1	Silicone	
3	Contact	1	Beryllium Bronze	Gold
2	Insulator	2	PTFE	
1	Body	1	Brass	Gold

**RoHS
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION
UNLESS OTHERWISE
NOTED TOLERANCES

APPROVED
TERRY

CHECKED
JOHN

DRAWN
JANE

SCALE 1:1 UNIT MM
DRAWN DATE 06 Apr. 2010

KEM KeMy Electronic Technology Inc.

TITLE
**SMA (F) Jack to MCX (F) Adapter,
Bulkhead, Waterproof**

DRAWING NO. **KM-030176-2**

REV 0