



Meets MIL-C-39012, CECC 22200, IEC 60169-17, IEC 60169-12, GB/T 15888.
Precision Machining and High Quality Grade Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC-1GHz
Working Voltage	<500V r.m.s	Withstanding Voltage	1500V r.m.s
Center Contact Resistance	≤5mΩ	Outer Contact Resistance	≤5mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.35
Durability	≥500 cycles	Temperature Range	-45°C to 125°C

3	Contact	1	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish
8				
7				
6				

**RoHS
Compliant**

© THIRD ANGLE PROJECTION

* MAJOR DIMENSION
UNLESS OTHERWISE
NOTED TOLERANCES

SCALE 1:1 UNIT MM

APPROVED
TERRY

CHECKED
JOHN

DRAWN
HENRY

DRAWN DATE
10 Apr. 2008

KEM KeMy Electronic Technology Inc.

TITLE
**TNC (F) Jack to UHF (F) Jack SO-239
Adapter**

DRAWING NO. **KM-030180**

REV
0