



Meets MIL-C-39012, IEC60169-15, IEC60169-16, CECC 22110, CECC 22210.
Precision Machining and High Quality Grade Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC-6GHz
Working Voltage	<335V r.m.s	Withstanding Voltage	1000V r.m.s
Center Contact Resistance	≤3mΩ	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.2
Durability	≥500 cycles	Temperature Range	-65°C to 165°C

3	Contact	1	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish
8				
7				
6				
5				
4				
3				

RoHS Compliant

THIRD ANGLE PROJECTION

* MAJOR DIMENSION
UNLESS OTHERWISE
NOTED TOLERANCES

SCALE 1:1 UNIT MM

APPROVED
TERRY

CHECKED
JOHN

DRAWN
HENRY

DRAWN DATE
01 Apr. 2011

KEM KeMy Electronic Technology Inc.

TITLE
N (M) Plug to RP SMA (M) Jack Adapter

DRAWING NO. **KM-030184**

REV
0