



RECOMMENDED
PANEL CUTOUT

Meets MIL-C-39012, CECC 22210, IEC60169-16. Precision Machining and High Quality Grade Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC-6 GHz
Working Voltage	1000V r.m.s	Withstanding Voltage	2500V r.m.s
Center Contact Resistance	≤1mΩ	Outer Contact Resistance	≤1mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.20
Durability	≥500 cycles	Temperature Range	-55°C to 155°C

6	Nut	1	Brass	Nickel
5	Washer	1	Brass	Nickel
4	Gasket	1	Silicone	
3	Contact	1	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel

**RoHS
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES	APPROVED TERRY
	CHECKED JOHN
	DRAWN HENRY
SCALE 1:1 UNIT MM	DRAWN DATE 16 Mar. 2011

APPROVED TERRY		KEM KeMy Electronic Technology Inc.	
CHECKED JOHN		TITLE N (F) Jack to N (F) Jack Adapter, Bulkhead, Waterproof	
DRAWN HENRY		DRAWING NO. KM-030304-3	
		REV 0	