



Part Number	Length (IN)	Length (MM)
KM-041107-0100	3.937±0.15	100±4
KM-041107-006I	6±3%	152.4±3%
KM-041107-001F	12±3%	304.8±3%

- Additional lengths can be provided by replacing XXXX to the desired length in MM, or XXXI in INCH, or XXXF in FEET.
- Any queries feel free to consult our sales team at sales@dgkemy.com

Specification:
 Frequency Range: 700~2700 MHz
 Impedance: 50Ω
 VSWR: ≤1.80
 Gain: 5-8 dBi
 Polarization: Vertical
 Temperature Range: -40°C to 80°C
 Durability: ≥500 cycles

4	Double-Wall Heat Shrink Tubing	1	Black
3	MMCX (M) Plug, R/A	1	KM-011114
2	FPC with Adhesive	1	KM-064006
1	Coaxial Cable	1	RG178
No.	Specification	QTY	Description

**RoHS
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES	SCALE	1:1	UNIT	MM
---	-------	-----	------	----

APPROVED TERRY
CHECKED JOHN
DRAWN HENRY
DRAWN DATE 05 Aug. 2010

KM KeMy Electronic Technology Inc.	
TITLE 4G Antenna, 700-2700 MHz, RG178, MMCX (M) Plug, R/A, Various Lengths	
DRAWING NO. KM-041107-XXXX	REV A