



| Part Number | Length (IN) | Length (MM) |
|----------------|-------------|-------------|
| KM-020237-0100 | 3.937±0.15 | 100±4 |
| KM-020237-006I | 6±3% | 152.4±3% |
| KM-020237-001F | 12±3% | 304.8±3% |

- Orient I-PEX MHF plug interface with respect to SMA 'D FLAT' as shown within $\pm 10^\circ$, orientation for cable length less than 150mm only.
- Additional lengths can be provided by changing XXXX to desired length in MM, or XXXI in INCH, or XXXF in FEET.
- Any queries feel free to consult our sales team at SALES@DGKEMY.COM

| | | | |
|-----|--------------------------|-----|---------------|
| 4 | Heat Shrink Tube | 1 | Black |
| 3 | IPEX MHF Plug | 1 | 20278-112R-13 |
| 2 | IP67/68 SMA (F) BHD Jack | 1 | KM-010114 |
| 1 | Coaxial Cable | 1 | 1.13mm |
| No. | Specification | QTY | Description |

RoHS
Compliant

THIRD ANGLE PROJECTION

* MAJOR DIMENSION
UNLESS OTHERWISE
NOTED TOLERANCES

SCALE1:1UNITMM

APPROVED
JOHN

CHECKED
TERRY

DRAWN
KEVIN

DRAWN DATE
13 Jul. 2008

KeMy Electronic Technology Inc.

TITLE
IP67/68 SMA (F) BHD Jack - 1.13mm -
IPEX MHF Plug, Various Lengths

DRAWING NO.
KM-020237-XXXX

REV
A