



Meets MIL-C-39012; CECC 22120; IEC 60169-8. Precision Machined with High-grade Quality Materials.

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC~4GHz
Working Voltage	<500V r.m.s	Withstanding Voltage	1500V r.m.s
Center Contact Resistance	≤1.5mΩ	Outer Contact Resistance	≤1mΩ
Insulation Resistance	≥5000MΩ	Center Conductor Retention Force	≥0.57N
Insertion Loss	≤0.20dB @ 3GHz	V.S.W.R.	≤1.25
Ferrule Hex Crimp Size	.128 (3.25mm)	Durability	≥500 cycles
Temperature Range	-55°C to 155°C		

4	Ferrule	1	Brass	Nickel
3	Contact	2	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish

**RoHS
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES			
SCALE	1:1	UNIT	MM

APPROVED TERRY
CHECKED JOHN
DRAWN HENRY
DRAWN DATE 16 Apr. 2009

KEM KeMy Electronic Technology Inc.	
TITLE BNC (F) Jack, for RG174, RG316	
DRAWING NO. KM-010410-174	REV 0