



Meets MIL-C-39012; CECC 22120; IEC 60169-8, Precision Machining and High Quality Material

**TECHNICAL CHARACTERISTICS**

Impedance	50Ω	Frequency Range	DC ~ 4GHz
Working Voltage	<500V r.m.s	Withstanding Voltage	1500V r.m.s
Center Contact Resistance	≤1.5mΩ	Outer Contact Resistance	≤1mΩ
Insulation Resistance	≥5000MΩ	Durability	≥500 cycles
Temperature Range	-55°C to 155°C	Ferrule Hex Crimp Size	.429 (10.9mm)
Weight	10.36g REF.		

4	Ferrule	1	Brass	Nickel
3	Contact	1	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish
8				
7				
6				

**RoHS  
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES			
APPROVED	JOHN	CHECKED	TERRY
DRAWN	HENRY	DRAWN DATE	10 Oct. 2011
SCALE	1:1	UNIT	MM

APPROVED	JOHN	KeMy Electronic Technology Inc.
CHECKED	TERRY	
DRAWN	HENRY	TITLE
		BNC (F) Jack, for RG8, LMR400
		DRAWING NO.
		KM-010410-400
		REV
		0