



Meets MIL-C-39012; CECC 22120; IEC 60169-8, Precision Machining and High Quality Material

TECHNICAL CHARACTERISTICS

Impedance	75Ω	Frequency Range	DC ~ 4GHz
Working Voltage	<500V r.m.s	Withstanding Voltage	1500V r.m.s
Center Contact Resistance	≤1.5mΩ	Outer Contact Resistance	≤1mΩ
Insulation Resistance	≥5000MΩ	Durability	≥500 cycles
Temperature Range	-55°C to 155°C	Ferrule Hex Crimp Size	.255 (6.48mm)
Weight	9.28g Ref.		

4	Ferrule	1	Brass	Nickel
3	Contact	1	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish
8				
7				
6				
5				
4				
3				

RoHS Compliant

* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES

APPROVED **JOHN**
 CHECKED **TERRY**
 DRAWN **HENRY**

THIRD ANGLE PROJECTION

SCALE 1:1 UNIT MM

DRAWN DATE 06 Sep. 2011

KEM KeMy Electronic Technology Inc.

TITLE **BNC (F) Jack, for RG59, RG62**

DRAWING NO. **KM-010410-59**

REV 0