



RECOMMENDED
PANEL CUTOUT

Precision Machining and High Quality Grade Material

MAJOR TECHNICAL CHARACTERISTICS

Impedance	75Ω	Frequency Range	DC-6GHz
Working Voltage	<170V r.m.s	Withstanding Voltage	500V r.m.s
Center Contact Resistance	≤5mΩ	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥10000MΩ	Durability	≥500 cycles
Temperature Range	-55°C to 125°C		

7	Nut	1	Brass	Nickel
6	Washer	1	Brass	Nickel
5	Gasket	1	Silicone	
4	Ferrule	1	Brass	Nickel
3	Contact	1	Phos. Bronze	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel

No.	Description	QTY	Material	Finish
-----	-------------	-----	----------	--------

**RoHS
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION
UNLESS OTHERWISE
NOTED TOLERANCES

SCALE 1:1 UNIT MM

APPROVED
TERRY

CHECKED
JOHN

DRAWN
KEVIN

DRAWN DATE
06 Mar. 2015

KEM KeMy Electronic Technology Inc.

TITLE
Micro BNC (F) Jack, BHD, Waterproof,
for Mini RG59, 4855R, 1855A

DRAWING NO. **KM-012904-1855**

REV
0