



Meets CECC 22340, IEC 61169-52
 Precision Machined with High-grade Quality Materials

MAJOR TECHNICAL CHARACTERISTICS

Impedance	50Ω
Frequency Range	DC-6GHz
Working Voltage	<170V r.m.s
Withstanding Voltage	500V r.m.s
Center Contact Resistance	≤5mΩ
Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥1000MΩ
VSWR	≤1.30
Durability	≥500 cycles
Temperature Range	-55°C to 155°C

4	Cover	1	Brass	Gold
3	Contact	1	Brass	Gold
2	Insulator	2	PTFE	
1	Body	1	Brass	Gold
No.	Description	QTY	Material	Finish

**RoHS
Compliant**

THIRD ANGLE PROJECTION

* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES			
SCALE	1:1	UNIT	MM

APPROVED
JOHN

CHECKED
TERRY

DRAWN
KEVIN

DRAWN DATE
12 Apr. 2009

KM KeMy Electronic Technology Inc.

TITLE
MMCX (M) Plug, R/A, for .086, RG405

DRAWING NO. **KM-011114-086**

REV
0