



Meets MIL-C-39012, CECC 22210, IEC60169-16. Precision Machining and High Quality Grade Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC-6 GHz
Working Voltage	1000V r.m.s	Withstanding Voltage	2500V r.m.s
Center Contact Resistance	≤1mΩ	Outer Contact Resistance	≤1mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.30
Ferrule Hex Crimp Size	.128 (3.25mm)	Durability	≥500 cycles
Temperature Range	-55°C to 155°C	Weight	35.57g ref.

8	Ferrule	1	Brass	Nickel
7	Nut	1	Brass	Nickel
6	Flat Washer	1	Brass	Nickel
5	Tooth Washer	1	Brass	Nickel
4	Gasket	1	Silicone	
3	Contact	2	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel

No.	Description	QTY	Material	Finish
-----	-------------	-----	----------	--------

RoHS Compliant	* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES		APPROVED JOHN	KM KeMy Electronic Technology Inc.	
			CHECKED TERRY		
			DRAWN HENRY	DRAWING NO. KM-010605-174	
			DRAWN DATE 27 Jul. 2010	REV 0	