



Meets MIL-C-39012, CECC 22210, IEC60169-16.
Precision Machined and High Quality Grade Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω
Frequency Range	DC-6GHz
Working Voltage	1000V r.m.s
Withstanding Voltage	2500V r.m.s
Center Contact Resistance	≤1mΩ
Outer Contact Resistance	≤1mΩ
Insulation Resistance	≥5000MΩ
VSWR	≤1.25
Durability	≥500 cycles
Temperature Range	-55°C to 155°C

8	Coupling Nut	1	Brass	Nickel
7	Nut	1	Brass	Nickel
6	Clamp	1	Brass	Nickel
5	Washer	2	Brass	Nickel
4	Gasket	1	Silicone	
3	Contact	1	Brass	Gold
2	Insulator	2	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish

RoHS Compliant	* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES		APPROVED TERRY	KEM KeMy Electronic Technology Inc.
			CHECKED JOHN	
			DRAWN HENRY	
THIRD ANGLE PROJECTION			TITLE N (M) Plug, Clamp, for RG213	
			DRAWING NO. KM-010608-213	
SCALE 1:1 UNIT MM			DRAWN DATE 06 Mar. 2011	REV 0