



Meets MIL-C-39012, CECC 22210, IEC60169-16. Precision Machined and High Quality Grade Material

**TECHNICAL CHARACTERISTICS**

Impedance	50Ω	Frequency Range	DC-3000MHz
Working Voltage	1000V r.m.s	Withstanding Voltage	2500V r.m.s
Center Contact Resistance	≤1mΩ	Outer Contact Resistance	≤1mΩ
Insulation Resistance	≥5000MΩ	Durability	≥500 cycles
Temperature Range	-55°C to 155°C		

3	Contact	1	Phosphorus Bronze	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish
8				

**RoHS  
Compliant**

© THIRD ANGLE PROJECTION

\* MAJOR DIMENSION  
UNLESS OTHERWISE  
NOTED TOLERANCES

SCALE 1:1 UNIT MM

APPROVED  
**JOHN**

CHECKED  
**TERRY**

DRAWN  
**KEVIN**

DRAWN DATE  
06 Mar. 2011

**KM** KeMy Electronic Technology Inc.

TITLE  
N (F) Jack, Clamp, for LMR600

DRAWING NO. **KM-010612-600**

REV  
0

All rights reserved. www.dgkemy.com

E  
D  
C  
B  
A

E  
D  
C  
B  
A

8 7 6 5 4 3 2 1