



Meets MIL-C-39012, CECC 22210, IEC60169-16. Precision Machined and High Quality Grade Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC-6GHz
Working Voltage	1000V r.m.s	Withstanding Voltage	2500V r.m.s
Center Contact Resistance	≤1mΩ	Outer Contact Resistance	≤1mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.25
Durability	≥500 cycles	Temperature Range	-55°C to 155°C
Weight	52.30g REF.		

7	Nut	1	Brass	Nickel
6	Clamp	1	Brass	Nickel
5	Washer	2	Brass	Nickel
4	Gasket	1	Silicone	
3	Contact	1	Brass	Gold
2	Insulator	2	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish

**RoHS
Compliant**

* MAJOR DIMENSION
UNLESS OTHERWISE
NOTED TOLERANCES

APPROVED
TERRY

CHECKED
JOHN

DRAWN
HENRY

DRAWN DATE
16 Apr. 2013

KEM KeMy Electronic Technology Inc.

TITLE
**N (F) Jack, 4-hole Flange Mount, Clamp,
for RG8X, LMR240**

DRAWING NO. **KM-010632-240** REV
0



THIRD ANGLE PROJECTION

SCALE 1:1 UNIT MM