


Meets MIL-C-39012, IEC60169-15, CECC 22110. Precision Machining and High Quality Grade Material.

**TECHNICAL CHARACTERISTICS**

Impedance	50Ω	Frequency Range	DC~3GHz
Working Voltage	<335V r.m.s	Withstanding Voltage	1000V r.m.s
Center Contact Resistance	≤3mΩ	Outer Contact Resistance	≤2.5mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.3
Durability	≥500 cycles	Temperature Range	-55°C to 155°C
Ferrule Hex Crimp Size	.128 (3.25mm)	Weight	3g



**RECOMMENDED  
PANEL CUTOUT**

6	Ferrule	1	Brass	Nickel
5	Nut	1	Brass	Nickel
4	Washer	1	Mn Steel	Nickel
3	Contact	1	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel
No.	Description	QTY	Material	Finish

<b>RoHS Compliant</b>	* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES	APPROVED <b>JOHN</b>	<b>KM</b> KeMy Electronic Technology Inc.
		CHECKED <b>TERRY</b>	
		DRAWN <b>KEVIN</b>	TITLE SMA (F) Jack, BHD, for RG174, RG316
		DRAWN DATE 05 Nov. 2013	DRAWING NO. KM-010106-174-N