



Meets MIL-C-39012, CECC 22200, IEC60169-17, Precision Machining and High Quality Material

TECHNICAL CHARACTERISTICS

Impedance	50Ω	Frequency Range	DC ~ 6GHz
Working Voltage	500V r.m.s	Withstanding Voltage	<1500V r.m.s
Center Contact Resistance	≤4mΩ	Outer Contact Resistance	≤1.5mΩ
Insulation Resistance	≥5000MΩ	VSWR	≤1.3
Durability	≥500 cycles	Temperature Range	-55°C to 155°C
Weight	12.13g Ref.		

7	Nut	1	Brass	Nickel
6	Clamp	1	Brass	Nickel
5	Washer	2	Brass	Nickel
4	Gasket	1	Silicone	
3	Contact	1	Brass	Gold
2	Insulator	1	PTFE	
1	Body	1	Brass	Nickel

No.	Description	QTY	Material	Finish
-----	-------------	-----	----------	--------

RoHS Compliant	* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES		APPROVED JOHN	KM KeMy Electronic Technology Inc.	
			CHECKED TERRY		TITLE TNC (F) Jack, Clamp, for RG58, LMR195
			DRAWN HENRY		DRAWING NO. KM-010537-58
THIRD ANGLE PROJECTION		SCALE 1:1	UNIT MM	DRAWN DATE 09 Apr. 2013	
				REV 0	