



Meets IEC60169-19, GB/T 15888. Precision Machined and High Quality Grade Material.

TECHNICAL CHARACTERISTICS

Impedance	Non-constant	Frequency Range	DC~300MHz
Working Voltage	<750V r.m.s	Withstanding Voltage	2000V r.m.s
Center Contact Resistance	≤5mΩ	Outer Contact Resistance	≤5mΩ
Insulation Resistance	≥5000MΩ	Center Conductor retention force	≥1.1N
Durability	≥500 cycles	Temperature Range	-40°C to 85°C

4	Nut	1	Brass	Nickel
3	Contact	1	Brass	Silver
2	Insulator	1	PTFE	Natural
1	Body	1	Brass	Silver
No.	Description	QTY	Material	Finish

**RoHS
Compliant**

☉ □ THIRD ANGLE PROJECTION

* MAJOR DIMENSION
UNLESS OTHERWISE
NOTED TOLERANCES

SCALE 1:1 UNIT MM

APPROVED
JOHN

CHECKED
TERRY

DRAWN
JANE

DRAWN DATE
13 Apr. 2013

KJM KeMy Electronic Technology Inc.

TITLE
UHF (M) PL-259 Plug, Twist-on, for
RG213

DRAWING NO. **KM-011305-213**

REV
0